

**MATERIAL SAFETY DATA SHEET**

**SECTION 1 - IDENTIFICATION**

**Product identifier** : **FPPF Octane Booster**

**Product Code(s)** : 00140, 90140, 00142  
Canadian Product Codes: 00425,90425

**Product Use** : Fuel additive

**Chemical Family** : Mixture.

**Supplier's name and address:** **FPPF Chemical Company, Inc.**  
117 West Tupper Street  
Buffalo, NY, USA  
14201

**Manufacturer's name and address:**  
Refer to Supplier

**Information Telephone #** : 1-800-735-3773

**24 Hr. Emergency Tel #** : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.).

**SECTION 2 - HAZARDS IDENTIFICATION**

**Classification** : OSHA: Hazardous classification: Flammable liquid; Acute Health Hazard; Chronic Health Hazard.

WHMIS classification: Class B2 (Flammable Liquids); Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material); Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

**Emergency Overview** : Colourless liquid. Solvent odor.  
Warning! Flammable liquid and vapor. May be harmful if inhaled. Inhalation may cause respiratory irritation and central nervous system depression. Could result in pulmonary edema (fluid accumulation). Causes skin and eye irritation. May be harmful or fatal if swallowed. May cause gastrointestinal discomfort. Aspiration can result in life-threatening lung injury. Contains material which can cause cancer.

**POTENTIAL HEALTH EFFECTS:**

**Signs and symptoms of short-term (acute) exposure**

*Inhalation* : Harmful by inhalation. Inhalation may cause respiratory irritation and central nervous system depression. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Inhalation of extremely high concentrations could cause pulmonary edema (fluid accumulation). Symptoms of pulmonary edema (chest pain, shortness of breath) may be delayed.

*Skin* : May cause mild to moderate skin irritation.

*Eyes* : May cause moderate to severe irritation.

*Ingestion* : Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

**Effects of long-term (chronic) exposure**

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

**Carcinogenic status** : Possible cancer hazard. See TOXICOLOGICAL INFORMATION, Section 11.

**Additional health hazards** : See TOXICOLOGICAL INFORMATION, Section 11.

**Potential environmental effects** : See ECOLOGICAL INFORMATION, Section 12.

**SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

<u>Ingredients</u>	<u>CAS #</u>	<u>Wt.%</u>
Aliphatic hydrocarbon petroleum naphtha	64742-88-7	60.00 - 100.00
Heavy aromatic solvent naphtha	64742-94-5	1.00 - 5.00

Methylcyclopentadienyl manganese tricarbonyl	12108-13-3	0.10 - 1.00
Naphthalene	91-20-3	0.10 - 1.00
Light aromatic solvent naphtha	64742-95-6	0.10 - 1.00
1,2,4-Trimethylbenzene	95-63-6	0.10 - 1.00
1,3,5-Trimethylbenzene	108-67-8	0.10 - 1.00

**SECTION 4 - FIRST AID MEASURES**

- Inhalation** : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention. Wash contaminated clothing before re-use.
- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes. If irritation or symptoms develop, seek medical attention.
- Ingestion** : Seek immediate medical attention/advice. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Notes For Physician** : Treat symptomatically.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Fire hazards/conditions of flammability** : Flammable liquid and vapor. This material may be ignited by heat, sparks and direct flame. Material will float on water and can be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.
- Flammability classification (OSHA 29 CFR 1910.1200)** : Flammable Liquid Class 1C.
- Oxidizing properties** : None known.
- Explosion data: Sensitivity to mechanical impact / static discharge** : May be sensitive to static discharge. Not expected to be sensitive to mechanical impact.
- Suitable extinguishing media** : Dry chemical, foam, carbon dioxide and water fog.
- Special fire-fighting procedures/equipment** : Firefighters should wear proper protective equipment and self contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.
- Hazardous combustion products** : Carbon oxides; Aldehydes; Hydrocarbons; irritating fumes and smoke.
- NFPA Rating** : 

0 - Minimal	1 - Slight	2 - Moderate	3 - Serious	4 - Severe
<i>Health:</i> 2	<i>Flammability:</i> 3	<i>Instability:</i> 0	<i>Special Hazards:</i>	0

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up.
- Environmental precautions** : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.
- Spill response/cleanup** : Ventilate area of release. Remove all sources of ignition. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.
- Prohibited materials** : Do not use combustible absorbents, such as sawdust.
- Special spill response procedures** : In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).  
US CERCLA Reportable quantity (RQ): Naphthalene (100 lbs / 45.4 kg)

**SECTION 7 - HANDLING AND STORAGE**

- Safe Handling procedures** : Use in a well ventilated area. Wear suitable protective equipment during handling. Do not ingest. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Use proper bonding and grounding techniques when transferring liquid. Avoid contact with incompatible materials. Wash thoroughly after handling.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.
- Incompatible materials** : Strong oxidizing agents; Acids.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

**SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**

<u>Exposure Limits</u>				
<u>Ingredients</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Aliphatic hydrocarbon petroleum naphtha	N/Av	N/Av	500 ppm (as petroleum distillates, naphtha)	N/Av
Heavy aromatic solvent naphtha	N/Av	N/Av	N/Av	N/Av
Methylcyclopentadienyl manganese tricarbonyl	0.2 mg/m <sup>3</sup> (Mn)	N/Av	0.2 mg/m <sup>3</sup> (final rule limit)	N/Av
Naphthalene	10 ppm	15 ppm	10 ppm ; 50 mg/m <sup>3</sup>	N/Av
Light aromatic solvent naphtha	N/Av	N/Av	N/Av	N/Av
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
1,3,5-Trimethylbenzene	N/Av	N/Av	N/Av	N/Av

- Ventilation and engineering measures** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.
- Respiratory protection** : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Confirmation of which type of respirator is most suitable for the intended application should be obtained from respiratory protection suppliers.
- Skin protection** : Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.
- Eye / face protection** : Chemical splash goggles are recommended. A full face shield may also be necessary.
- Other protective equipment** : Wear resistant clothing and boots. Other equipment may be required depending on workplace standards. An eyewash station and safety shower should be made available in the immediate working area.
- General hygiene considerations** : Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Physical state** : liquid
- Appearance** : Colourless liquid.
- Odour** : Solvent odor.
- Odour threshold** : N/Av
- pH** : N/Av
- Boiling point** : N/Av
- Specific gravity** : 0.82
- Melting/Freezing point** : N/Av
- Coefficient of water/oil distribution** : N/Av

<b>Vapour pressure (mmHg @ 20° C / 68° F)</b>	: N/Av	<b>Solubility in water</b>	: N/Av
<b>Vapour density (Air = 1)</b>	: >1	<b>Evaporation rate (n-Butyl acetate = 1)</b>	: <1
<b>Volatile organic Compounds (VOC's)</b>	: N/Av	<b>Volatiles (% by weight)</b>	: N/Av
<b>Flash point</b>	: 26°C / 79°F	<b>Auto-ignition temperature</b>	: N/Av
<b>Flash point Method</b>	: Tag closed cup	<b>Upper flammable limit (% by vol.)</b>	: N/Av
<b>Lower flammable limit (% by vol.)</b>	: N/Av	<b>Flashback observed</b>	: N/Av
<b>Flame Projection Length</b>	: N/Av		

**Section 10: Stability And Reactivity**

<b>Stability and reactivity</b>	: Stable under the recommended storage and handling conditions prescribed.
<b>Hazardous polymerization</b>	: Will not occur.
<b>Conditions to avoid</b>	: Avoid heat and open flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas.
<b>Materials To Avoid And Incompatibility</b>	: See Section 7 (Handling and Storage) section for further details.
<b>Hazardous decomposition products</b>	: None known, refer to hazardous combustion products in Section 5.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

<b>Target organs</b>	: Eyes, skin, respiratory system, digestive system, central nervous system.
<b>Routes of exposure</b>	: <i>Inhalation:</i> YES <i>Skin Absorption:</i> NO <i>Skin &amp; Eyes:</i> YES <i>Ingestion:</i> YES
<b>Toxicological data</b>	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<b>Ingredients</b>	<b>LC<sub>50</sub>(4hr)</b>	<b>LD<sub>50</sub></b>	
	<b>inh, rat</b>	<b>(Oral, rat)</b>	<b>(Rabbit, dermal)</b>
Aliphatic hydrocarbon petroleum naphtha	N/Av	N/Av	N/Av
Heavy aromatic solvent naphtha	>590 mg/m <sup>3</sup>	N/Av	>1800 mg/kg
Methylcyclopentadienyl manganese tricarbonyl	8.5 ppm	22.9 mg/kg	140 mg/kg
Naphthalene	N/Av	1780 mg/kg	>2500 mg/kg
Light aromatic solvent naphtha	N/Av	>5000 mg/kg	>3160 mg/kg
1,2,4-Trimethylbenzene	18 g/m <sup>3</sup>	5000 mg/kg	N/Av
1,3,5-Trimethylbenzene	24000 mg/m <sup>3</sup>	5000 mg/kg	N/Av

<b>Carcinogenic status</b>	: Contains Naphthalene. Naphthalene is classified as carcinogenic by IARC (Group 2B) and NTP (Group 2 - Reasonably anticipated).
<b>Reproductive effects</b>	: Not expected to be cause reproductive effects.
<b>Teratogenicity</b>	: Not expected to be a teratogen.
<b>Mutagenicity</b>	: Not expected to be mutagenic in humans.
<b>Epidemiology</b>	: Not available.
<b>Sensitization to material</b>	: Not expected to be a skin or respiratory sensitizer.
<b>Synergistic materials</b>	: Not available.
<b>Irritancy</b>	: May cause eye, skin and respiratory tract irritation.
<b>other important hazards</b>	: None known or reported by the manufacturer.
<b>Conditions aggravated by overexposure</b>	: Pre-existing skin, eye, respiratory and central nervous system disorders.

**SECTION 12 - ECOLOGICAL INFORMATION**

<b>Ecotoxicity</b>	: No data is available on the product itself.
<b>Mobility</b>	: No data is available on the product itself.



MSDS Preparation Date (dd/mm/yyyy): 24/03/2010

Page 5 of 7

**Persistence** : No data is available on the product itself.**Bioaccumulation potential** : No data is available on the product itself.**Other Adverse Environmental effects**

: The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

**SECTION 13 - DISPOSAL CONSIDERATIONS****Handling for Disposal** : Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.**Methods of Disposal** : Dispose of in accordance with federal, provincial and local hazardous waste laws.**RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.**SECTION 14: TRANSPORT INFORMATION**

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
49CFR/DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (Aliphatic naphtha)	3	III	
<b>49CFR/DOT Additional information</b>	Not regulated for rail or road shipment if packaged in non-bulk containers (450 Litres or less each). Limited quantity exemption may be used if product is in containers of 5 Litres or less, per section 173.150 of 49 CFR.				
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Aliphatic naphtha )	3	III	
<b>TDG Additional information</b>	This material may be shipped as non-regulated material when in small means of containment (<450 Litres), provided the requirements of TDG section 1.33 are met.				

**SECTION 15 - REGULATORY INFORMATION****US Federal Information:**

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

This material is classified as hazardous under OSHA regulations (29CFR 1910.1200). See Section 2.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: Naphthalene; 1,2,4-Trimethylbenzene

**US State Right to Know Laws:**

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

**International Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). See Section 2.


This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating** : \* - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe  
*Health: \*2 Flammability: 3 Reactivity: 0*

**Legend** : ACGIH: American Conference of Governmental Industrial Hygienists  
 CAS: Chemical Abstract Services  
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
 CFR: Code of Federal Regulations  
 DOT: Department of Transportation  
 EPA: Environmental Protection Agency  
 HMIS: Hazardous Materials Identification System  
 HSDB: Hazardous Substances Data Bank  
 IARC: International Agency for Research on Cancer  
 Inh: Inhalation  
 MSHA: Mine Safety and Health Administration  
 N/Ap: Not Applicable  
 N/Av: Not Available  
 NFPA: National Fire Protection Association  
 NIOSH: National Institute of Occupational Safety and Health  
 NTP: National Toxicology Program  
 OSHA: Occupational Safety and Health Administration  
 PEL: Permissible exposure limit  
 RCRA: Resource Conservation and Recovery Act  
 RTECS: Registry of Toxic Effects of Chemical Substances  
 SARA: Superfund Amendments and Reauthorization Act  
 STEL: Short Term Exposure Limit  
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
 TLV: Threshold Limit Values  
 TPQ: Threshold Planning Quantity  
 TSCA: Toxic Substance Control Act  
 TWA: Time Weighted Average  
 WHMIS: Workplace Hazardous Materials Identification System

**References** : 1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2009  
 2. International Agency for Research on Cancer Monographs, searched 2009  
 3. Canadian Centre for Occupational Health and Safety, CCHInfoWeb databases (Chempendium, HSDB and RTECs).  
 4. Material Safety Data Sheet from manufacturer.  
 5. US EPA Title III List of Lists  
 6. California Proposition 65 List

<p><b>Prepared for:</b>                  FPPF Chemical Company, Inc.                  117 West Tupper Street                  Buffalo, NY, USA 14201                  Telephone: 1-800-735-3773                  Please direct all enquiries to FPPF Chemical Company</p>	
<p><b>Prepared by:</b>                  ICC The Compliance Center Inc.  <a href="http://www.thecompliancecenter.com">http://www.thecompliancecenter.com</a></p>	

**DISCLAIMER OF LIABILITY**

MSDS Preparation Date (dd/mm/yyyy): 24/03/2010

Page 7 of 7

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from FPPF Chemical Company, Inc and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and FPPF Chemical Company, Inc.

**Preparation Date (dd/mm/yyyy)**

: 24/03/2010

**END OF DOCUMENT**